

METABO KHE 2443 ROTARY HAMMER DRILL



Features:

- High performance hammer action, precisely mounted in a housing made of aluminium alloy: long-lasting and robust
- Hammer stop for drilling in rotary only mode
- Rotation stop for chiselling
- Clockwise and anti-clockwise rotation
- Stoppable switch for trouble-free chiselling in continuous operation
- Vario (V)-Electronics for working with customised speeds for the materials used
- Metabo S-automatic torque limiting clutch: mechanical decoupling of the drive if the drill jams for safe working

Specifications:

- Drill diameter in:
 - Concrete with hammer drills - 15/16 "
 - Masonry with core bits - 2 5/8 "
 - Steel - 1/2 "
 - Soft wood - 1 3/16 "
- Idle revolution - 0 - 1150 /min
- Rated input power - 800 W
- Output power - 410 W
- Revolutions at rated load - 960 /min
- Maximum impact rate - 5400 /min
- Max. single blow energy (EPTA) - 2.3 J
- Impact power - 166 J/s
- Collar diameter - 1 11/16 "
- Bit retainer - SDS-plus
- Weight (without power cable) - 3 Kg
- Cable length - 4 m

Includes:

- Hammer chuck for tools with SDS-plus shank end
- Side handle
- Drilling depth guide
- Plastic carry case