

## MT 18 LTX (613021890) Cordless Multi-Tool

18V; Cardboard box

Order no. 613021890 EAN 4007430277558



Product may differ from Image





- Oscillating cordless multi-tool with high performance comparable to that of a mains powered version
- Indispensable for interior construction work such as cutting, sanding, scraping and grating of different materials
- Tool holder for maximum compatibility to OIS, Starlock and other accessories
- Metabo Quick tool change system for time-saving, convenient change of accessories
- Fast and powerful thanks to the combination of a large oscillation angle of 3.2° and VTC-Electronics to maintain constant speed even under load
- Extra bright double LED lights for good visibility of the working area
- Slim design and non-slip soft-grip surface for optimised handling
- Extraction possibility by means of connecting an all-purpose vacuum cleaner
- Battery packs with capacity display for checking the charge status
- Ultra-M technology: highest performance, gentle charging and 3 years of warranty on the battery pack.

| Technical data                               |                  |
|--|------------------|
| Characteristics                              |                  |
| Battery pack voltage                         | 18 V             |
| Orbital frequency with no load               | 7000 - 18000 rpm |
| Oscillation angle left/right                 | 1.6 °            |
| Base plate, dimensions from corner to corner | 93 mm / 3 5/8 "  |
| Weight (including battery pack)              | 1.8 kg / 4 lbs   |

www.metabo.com 1 / 2



## **Vibration**

| Surface grinding                   | 7.5 m/s <sup>2</sup>  |
|------------------------------------|-----------------------|
| Uncertainty of measurement K       | 1.5 m/s <sup>2</sup>  |
| Scraping                           | 11.5 m/s²             |
| Uncertainty of measurement K       | 1.5 m/s <sup>2</sup>  |
| Sawing with plunge cut saw blade   | 13 m/s²               |
| Sawing with segmented sawing blade | 11.6 m/s <sup>2</sup> |
| Uncertainty of measurement K       | 3 m/s²                |
| Noise emission                     |                       |
| Sound pressure level               | 77 dB(A)              |
| Sound power level (LwA)            | 88 dB(A)              |
| Uncertainty of measurement K       | 3 dB(A)               |

## Scope of delivery

Plunge saw blade 32 mm HCS (wood)

Triangular hook and loop sanding plate 93 mm

5 Hook and loop sanding sheets 93 mm P 80

5 Hook and loop sanding sheets 93 mm P 120

Suction adapter

Multi-adapter

MetaLoc case insert

(without battery pack, without charger)



www.metabo.com 2 / 2