# **Portable Generators**

Power - when you need it - where you need it







# **W** Westinghouse

# The Westinghouse Story



George Westinghouse 1846-1914

In 1886, the American inventor and entrepreneur George Westinghouse amazed the world by introducing the alternating current (AC) electrical system. Today, this same system still provides all your electric light and power needs.

The Westinghouse Electric Corporation he founded continues to improve our lives through unparalleled leadership in commercial electrical energy technologies.

With a proven track record of providing the safest, most advanced

and cost effective solutions,
Westinghouse is working to provide
safe, clean and reliable power for the
world's ever-increasing energy needs.

For more than 125 years, continuous innovation has enabled Westinghouse to expand beyond its traditional utility electric power systems.

Today Westinghouse also serves the world with a broad range of electric motors, consumer electronics, lighting fixtures, home appliances, HVAC systems, solar power systems, and portable power products.

## Westinghouse Portable Generators

Building on the success of Westinghouse portable electric generators in the USA, we are proud to offer a brand new range of portable generators designed specifically for the Australian market.

These units have been developed from the ground up to meet the demanding operating conditions and safety regulations unique to Australia.

When you need portable back-up power for your home or workplace, or a portable power supply on your farm or job site, Westinghouse has a portable generator that's right for you.

The range covers maximum electrical power outputs from 3,750 Watts up to a class-leading 8,500 Watts.

Company Maler 1996 or 1996 or

To ensure high fuel efficiency and low noise operation, all models are powered by advanced 4-stroke petrol engines.

The Utility Series generators are compact, high performance units equipped with all the features Australian users expect today.

Our Professional Series generators go even further by offering you the increased electrical safety of a RCD safety switch and weatherproof 240 Volt outlet(s).

Westinghouse portable generators are designed for easy use and include everything you need to get started right out of the box.

You can rely on the support provided by our Australia-wide dealer network offering product selection advice, maintenance and repair services, as well as genuine spare parts.

To ensure the lasting quality of your ownership experience, all models are covered by a comprehensive factory-backed 2 year or 500 hour parts and labour warranty (conditions apply).

The Westinghouse brand represents quality, value, integrity and heritage – values we've incorporated into the design and manufacture of all our portable electric generators.

Power - when you need it - where you need it.





# Portable Generator Range



## **Utility Series**



## **Professional Series**





# **Unique Features**

Westinghouse portable generators come fully loaded with a unique combination of high quality features, altogether offering you superior value for money.

Each component has been carefully designed and manufactured to optimise its contribution to the performance, reliability and safety of the overall unit. The innovation you expect from Westinghouse is clearly evident in these state-of-the-art portable generators that have redefined the industry's benchmark.

Your choice is easy - select from the richly equipped Utility Series or opt for the ultimate safety offered by the WH&S compliant Professional Series.



## Advanced 4-Stroke Engine

The reliable heart powering each Westinghouse generator is a high output, fuel efficient, overhead valve (OHV), air-cooled petrol engine.



#### Low Oil Shutdown

To safeguard your investment, all models are fitted with an automatic shutdown system that is triggered in the event of low engine oil level.



#### Pulse-Flo Muffler

Our generators are amongst the quietest thanks to the exclusive Pulse-Flo muffler, which also has a spark arrester for fire prevention.



#### **Anti-Vibration Mounts**

The engineered anti-vibration mounts isolate the engine and alternator from the frame to reduce noise emissions and transmitted dynamic loading.



#### One Touch Electric Start\*\*

No need to look for the key. Your electric start generator can be up and running in seconds by pressing a single button.

Pictured without weatherproof cover.




## Maintenance Free Battery\*\*

Designed for maximum starting power and reliability, the compact 12 Volt battery is a sealed-for-life unit supplied as standard on electric start models.



## Copper Wound Alternator

Westinghouse alternators generate more electrical power at the output terminals because of the superior conductivity of their all-copper windings.



## **AVR System**

To protect your electrical devices, the Auto Voltage Regulator (AVR) provides precise and stable control of the generator's 240 Volt sine wave output.



## RCD Safety Switch\*

The best protection money can buy. The RCD safety switch protects against 240 Volt electric shock that can cause serious injury or death.



#### **Electrical Circuit Breakers**

Overload protection of the generator's 240 Volt and 12 Volt electrical systems is reliably provided by quick acting circuit breakers.

Pictured without weatherproof covers.



#### Weatherproof Outlets\*

Single or twin 240 Volt, 15 Amp outlets are provided for connecting either standard plugs or heavy-duty weatherproof IP66 plugs.



#### Weather Resistant Outlets

Twin 240 Volt, 15 Amp outlets are provided for connecting standard 10 Amp or 15 Amp plugs.



#### 12 V DC Socket

Power your mobile phone, notebook computer or recreational device from the handy cigarette lighter type socket rated at 100 Watts.



## Plug & Play

Just add petrol and you're ready to go. Everything for your new Westinghouse generator is supplied in the carton. Some assembly required.

## **Unique Features**





## High Capacity Fuel Tank

Refuel less often and keep running longer thanks to the large capacity fuel tank and the engine's low fuel consumption.



## Fuel Level Gauge

Never run out of fuel again thanks to the easy-to-read fuel gauge that's fitted as standard on all of these Westinghouse portable generators.



## Easy Grip Fuel Cap

The easy grip fuel cap can be handled even if wearing gloves while the builtin fuel strainer prevents the ingress of water and other contaminants.



## High Leverage Handles

For operator comfort, the high leverage fold-down handles are fitted with antislip rubber grips and can be easily stored out of the way when not in use.



### **Puncture Proof Tyres**

No more annoying flat tyres to slow you down. Your generator is fitted with long wearing, puncture proof tyres mounted on impact resistant, rust proof wheels.



#### Welded Steel Roll Frame

For ease of handling and rugged protection against damage, all models are built with a heavy duty, fully-welded steel roll frame.

\* Professional Series only. \*\* Electric start models only.



### **Utility Series Control Panel**

All the electrical controls and outlets as well as the engine control switch are clearly labelled and ergonomically positioned for safe and easy use.



## Professional Series Control Panel

The RCD safety switch and weatherproof 240 Volt outlet(s) are logically integrated into the panel layout for intuitive operator control.



Voltage

8888

Frequency



Run Time

## **Digital VFT Meter**

An innovative digital VFT meter displays the generator's AC output voltage and frequency and also the total running hours.

#### Colour Coded Touch Points

Westinghouse portable generators are designed to be very easy to start. Simply follow the visual instructions marked on the unit that guide you to the yellow coloured touch points in their correct sequence.



Oil Fill Plug / Dipstick

MAINING

THE PROPERTY OF THE P







Fuel Level Gauge Choke Lever

Engine Control Switch

Recoil Starter Handle



## **Generator Selection Guide**

## Follow These Steps

- 1. Identify the devices you want to power simultaneously. Record the starting power and running power demands of each device in Watts.
- 2. Add up the running power of all devices. This total must be less than the generator's rated running power output.
- 3. Identify the device with the highest starting power demand. Add this value to the running power demands of the other devices. This total must be less than the generator's rated starting power output.
- 4. Select either a Professional or Utility Series generator for standalone plug and socket connection to portable electric devices. The RCD safety switch equipped PRO models offer you the best protection against electric shock as per Australian WH&S Regulations.
- 5. Or select a Utility Series generator if your application requires it to be connected to a fixed electrical installation by a licensed electrician. The RCD safety switch fitted to the PRO models will trip on load if connected to a multiple earthed neutral (MEN) electrical installation.

## **Typical Power Demands**

The adjoining table is an approximate guide to the running and starting power demands of common electrical devices.

There are large variations in the performance of different makes and models of electrical devices and the manufacturers specifications are often inaccurate or misleading. High power, low duty cycle devices such as welders and plasma cutters are especially problematic in this regard.

It is recommended that the generator and powered device(s) be trialled to ensure that the combination performs to your satisfaction.



Device	Running Power (Watts)	Starting Power (Watts)	
Bathroom			
Hot Water System - 250 L	3,600	3,600	
Climate Control			
A/C - Portable / Window Type 2.8 kW	1,200	2,100	
A/C - Split System 5.2 kW Fixed Speed	1,900	6,650	
A/C - Split System 5.2 kW Inverter	1,500	1,500	
Fan - Ceiling or Personal	60	210	
Heater - 1,000 W	1,000	1,000	
Heater - 2,400 W	2,400	2,400	
Construction			
Air Compressor - 1.65 kW	2,200	7,700	
Air Compressor - 2.4 kW	3,300	11,550	
Angle Grinder - 180 mm	1,800	2,160	
Circular Saw - 270 mm	1,800	2,160	
Concrete Mixer - 100 L	1,300	1,560	
Concrete Vibrator - 50 mm	1,900	6,650	
Demolition Breaker - 30 kg	1,900	2,280	
Drill - 13 mm	750	900	
Orbital Sander - 1/3 Sheet	200	240	
Planer - 82 mm	850	1,020	
Rotary Hammer Drill - 26 mm	850	1,020	
Submersible Pump - 50 mm	2,200	7,700	
Entertainment			
Hi-Fi System	100	100	
TV - Large Screen	200	200	
Kitchen			
Coffee Machine	1,450	1,450	
Cooktop - Large Element	2,400	2,400	
Cooktop - Small Element	1,200	1,200	
Dishwasher	1,800	2,400	
Kettle	2,400	2,400	
Microwave	1,000	1,000	
Oven	3,100	3,100	
Refrigerator / Freezer - Full Size	200	700	
Toaster	1,000	1,000	
Water - Boiler, 3 L	1,500	1,500	
Water - Chiller, Free-Standing	200	700	
Laundry			
Clothes Dryer	2,400	2,880	
Washing Machine	1,200	1,800	
Lighting			
Fluorescent Lamp 20 W	20	20	
Incandescent Bulb 100 W	100	100	
Maintenance			
Battery Charger - 12 V, 5.4 A	100	100	
Drain Cleaner Snake	400	1,400	
Pressure Washer - 10 MPa, 600 L/h	2,400	8,400	
Vacuum Cleaner	2,200	2,640	
Office	I		
Computer with LCD Monitor	150	150	
Inkjet Fax / Printer	50	50	
iPad / iPhone Charger	12	12	
Laser Fax / Printer	900	900	
Photocopier	1,500	1,500	
Scanner	30	30	
Security			
Garage Door Opener	200	240	

# **Specifications**

















Width Length					•			
PARAMETER	WHXC3750	WHXC5000	WHXC7000	WHXC8500E	WHXC3750-PRO	WHXC8500E-PR		
ENGINE								
Туре	1-Cylinder, 4-Stroke, Overhead Valve, Air Cooled, Unleaded Petrol							
Displacement (cm³)	208	292	357	420	208	420		
Low Oil Shutdown	V	~	V	~	V	V		
Fuel Tank (Litres)	15	25	25	25	15	25		
Fuel Gauge	V	~	~	~	~	V		
Run Time @ 50% Load (hours)	16.8	18.7	15.3	13.1	16.8	13.1		
Starting Method	Manual	Manual	Manual	Electric	Manual	Electric		
Battery	N/A	N/A	N/A	~	N/A	~		
240 VOLT AC ELECTRICAL								
Running Power (Watts)	3,000	4,000	5,500	6,750	3,000	6,750		
Starting Power (Watts)	3,750	5,000	7,000	8,500	3,750	8,500		
Max. Output @ 0.8 PF (kVA)*	4.7	6.3	8.8	10.6	4.7	10.6		
Max. Running Current (Amps)	12.5	16.7	22.9	28.1	12.5	28.1		
Voltage Control	Automatic Voltage Regulator (AVR), Sine Wave Output							
Outlets	2 × 15 A, IP44	2 × 15 A, IP44	2 × 15 A, IP44	2 × 15 A, IP44	1 × 15 A, IP66	2 × 15 A, IP66		
Overload Circuit Breakers	V	V	V	V	V	~		
RCD Safety Switch	×	×	×	×	V	~		
Digital VFT Meter	V	~	V	~	V	V		
IP23 Electrical Enclosure	V	~	V	~	V	~		
12 VOLT DC ELECTRICAL			,					
Maximum Power (Watts)	100							
Maximum Current (Amps)	8.3							
Overload Circuit Breaker	V	~	~	~	~	<b>V</b>		
ACCESSORIES								
Wheels & Handles	~	V	V	V	~	V		
Engine Oil & Spark Plug Tool	V	~	~	~	~	~		
DIMENSIONS, WEIGHT & NO	ISE							
Dimensions L × W × H (cm)	65 × 60 × 56	74 × 70 × 66	74 × 70 × 66	74 × 70 × 66	65 × 60 × 56	74 × 70 × 66		
Weight - Dry (kg)	52	71	80	94	52	94		
Noise Level @ 7m (dB (A))**	76	76	80	80	76	80		

<sup>\*</sup> Theoretical value for comparison. \*\* Measured at 100% load.

# **Optional Accessories**



#### **Protective Covers**

Safeguard your generator during transport or storage.

- Heavy duty, UV stabilized PVC fabric.
- Oil, petrol and tear resistant.
- Bottom fastening strap and buckle.

**Product Codes:** GC634847 (WHXC3750/PRO) GC745453 (WHXC5000 & above)

